

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification 6 : B29C 47/12, 49/00, 33/36</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/17916</p> <p>(43) International Publication Date: 15 April 1999 (15.04.99)</p>
<p>(21) International Application Number: PCT/CA98/00903</p> <p>(22) International Filing Date: 1 October 1998 (01.10.98)</p> <p>(30) Priority Data: 08/943,120 3 October 1997 (03.10.97) US</p> <p>(71)(72) Applicants and Inventors: LUPKE, Manfred, A., A. [CA/CA]; 92 Elgin Street, Thornhill, Ontario L3T 1W6 (CA). LUPKE, Stefan, A. [CA/CA]; 32 Vintage Lane, Thornhill, Ontario L3T 1X6 (CA).</p> <p>(74) Agents: JEFFREY, John, C. et al.; Suite 301, 133 Richmond Street West, Toronto, Ontario M5H 2L7 (CA).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: MOLDING APPARATUS WITH DOWNWARDLY MOVING MOLD TUNNEL

(57) Abstract

A plastic molding apparatus comprises an extruder (3) and a vertically extending mold tunnel (20) formed by mated mold block sections which are moved downwardly through the mold tunnel (20) as part of a continuous looping of the mold block sections around the apparatus. The mold tunnel has an upwardly opening mouth and the extruder (3) feeds a stream of molten plastic (13) downwardly into the mouth of the mold tunnel (20).



TITLE: MOLDING APPARATUS WITH DOWNWARDLY MOVING MOLD TUNNELFIELD OF THE INVENTION

5 The present invention relates to a plastic mold apparatus of the type in which a continuous stream of molten plastic is fed to a moving mold tunnel.

10 BACKGROUND OF THE INVENTION

 A known molding apparatus is one in which an extruder feeds a continuous stream of molten plastic to a horizontally extending mold tunnel. This type of apparatus is very beneficial for example in a formation of plastic
15 pipe. It is not however well suited for the formation of irregularly shaped plastic articles which require variable positioning of the feed of the plastic to the mold tunnel.

 Although very rare vertically operating extruders
20 are known, as described in United States patent 3,519,705 and U.K. Patent 2,134,844A. The extruders in both of these patents operate using blow molding and as such the product shaping regions known as mold tunnels must be sealed. Furthermore, the extruders in these two patents are trapped
25 within the upper end of the mold tunnels prohibiting positional adjustments of the extruder relative to the mold tunnel.

SUMMARY OF THE INVENTION

30 The present invention provides a plastic molding apparatus comprising an extruder and a vertically extending mold tunnel formed by mated mold block sections which are moved downwardly through the mold tunnel as part of a continuous looping of the mold block sections around the
35 apparatus. The mold tunnel has an upwardly opening tunnel mouth and the extruder feeds a stream of molten plastic downwardly into the mouth of the mold tunnel.

The apparatus of the present invention is particularly useful in the molding of irregularly shaped articles because either the mold tunnel and/or the extruder
5 can be easily adjusted in position while maintaining feed of the plastic from the extruder to the mold tunnel in meeting the requirements of forming irregularly shaped plastic parts.

BRIEF DESCRIPTION OF THE DRAWINGS

The above as well as other advantages and features of the present invention will be described in greater detail according to the preferred embodiments of the present invention in which;

Figure 1 is a side view of a molding apparatus according to a preferred embodiment of the present invention;

Figure 2 is an enlarged side view of the upper mold tunnel region of the apparatus of Figure 1;

Figures 3 and 4 are sectional views along the lines 3-3 and 4-4 respectively of Figure 2.

DETAILED DESCRIPTION ACCORDING TO THE PREFERRED EMBODIMENTS OF THE PRESENT INVENTION

Figure 1 shows a plastic molding apparatus generally indicated at 1. This apparatus comprises an extruder 3 which feeds a molten stream of plastic 13 to a product shaping region generally indicated at 15. In the particular embodiment shown, the product shaping region comprises a pair of side by side endless loop carrier tracks 17 and 19. A plurality of mold block sections are secured around each of the carrier tracks. The carrier tracks move the mold block sections to a central mold tunnel 20 where the mold block sections on one track close and mate with the mold block sections on the other carrier track. As will be seen in Figure 1, the mold tunnel 20 is vertically extending and the mold block sections when mated with one another move downwardly through the mold tunnel. The tunnel mouth is at the upper end of the mold tunnel where the stream of plastic 13 feeds into the mold tunnel.

Each of the tracks is driven by a gear 18 at one end of each track. Figure 2 shows the drive gears 18 as being at the upper ends of the continuously looped, tracks however, it is equally possible to provide the drive gears

at the lower ends of the tracks. It may also be desirable to provide drive gears at each end of both tracks.

The movement of the tracks is extremely efficient
5 and requires very little in the way of a driving force. As
will be understood from the drawings, each track with its
mold blocks is balanced from side to side such that the
amount of lift required to move the mold block sections
upwardly on one side of each track is effectively offset by
10 the weight of the mold block sections moving downwardly on
the other side of each track.

A number of features are produced as a result of
the vertical orientation of the apparatus of the present
15 invention. One of those advantages is that the apparatus
takes up less floor space than a conventional horizontally
operating extrusion type molding apparatus.

Even more important to the present invention is the
20 ease with which the extruder can be lined up with the mold
tunnel and more specifically the mouth of the mold tunnel.
Furthermore, the extruder feeds through gravity down into
the mold tunnel which requires less working pressure at the
extruder. In addition, the actual extrusion nozzle 6 of
25 the extruder does not have to be trapped within the mold
tunnel but rather can be positioned remotely thereof as
shown in Figure 1 which again enhances the ability to align
the extruder with the mold tunnel should movement be
required of either as described below. In such a case the
30 molding will be preferably achieved by vacuum within the
mold tunnel.

Extrusion apparatus 1 is particularly well suited
for the formation irregularly shaped articles such as
35 bottles, automotive parts or any other type of plastic
molded article.

In the embodiment shown, carrier tracks 17 and 19 are, as described above, used to move a plurality of mold block sections. These mold block sections include different sets of mold block sections which mate with one another in the mold tunnel. The different sets of mold block sections may have different configurations according to the shape of the plastic article to be formed. For example, mold block section 21 on track 17 mates in the mold tunnel with mold block section 25 on track 19 as shown in Figure 3 of the drawings. Mold block section 21 has an interior mold cavity 22 and mold block section 25 has an interior mold cavity 26. As these two mold block sections are brought by their respective carriers to the upper end of the mold tunnel where they close with one another as shown in Figure 3, the mouth of the mold tunnel is formed by the mating of the mold cavities 22 and 26. The stream 13 of molten parison is then fed from the extruder 3 into the mouth of the mold tunnel having this shape and being in a specific position below the extruder.

20

The shape and positioning of the tunnel mouth is not however always the same as what is shown in Figure 3. For example, tracks 17 and 19 are provided with a different set of mold block sections 23 and 27 which also mate with one another in the mold tunnel. Mold block section 23 has an interior cavity 24 while mold block section 27 has an interior cavity 28 as shown in Figure 4 of the drawings. When these two mold block sections are brought around to the top of the mold tunnel they will form the mold tunnel mouth of a different shape than what is shown in Figure 3. In addition, the positioning of the mouth of the mold tunnel has shifted in a horizontal plane from the Figure 3 to the Figure 4 position. Note that the shifting, as evidenced by the parting line 22 in figure 2 of the mold block sections, is gradual so that the full mouth of the tunnel is exposed.

35

In view of the above described shifting of the tunnel mouth it is important that the apparatus be capable of adjustment to ensure that the flow of plastic from the extruder goes directly into the mouth of the mold tunnel regardless of its shape and position. This is achievable in a number of different ways as described later below. However, it should be noted at this point that each of the adjustments is easily made because of the vertical orientation of the mold tunnel, the separation of the extruder from the mold tunnel and the ability of the extruder to feed downwardly into the mold tunnel.

As will be seen in Figure 1, extruder 3 is held in its downwardly directed position by an extruder support 9. The extruder head itself may be adjustably secured as indicated at 4 to the support 9 which allows horizontal or side to side adjustment of the extruder head as indicated by arrows 5 and 7.

It is also possible to have the base of the extruder support 9 seated on adjustment members 11 on the ground surface for the support. This again would provide a side to side adjustment of the extruder head.

Another method of ensuring alignment of the plastic flow to a variably positioned tunnel is by making the mold block carrier tracks 17 and 19 movable in a horizontal plane. In the embodiment shown, the two tracks are held by support beams 33 of a carrier support 29. The carrier tracks are adjustable along beams 33 in the direction of arrows 35 and 37. During the mold operation, the two tracks will move simultaneously with one another to keep the mold tunnel closed. However, during down times, either one or both of the carrier tracks are movable along beams 33 independently of one another in opposite directions to separate the two tracks for cleaning and/or replacement of the mold block sections.

As also shown in Figure 1, the entire support 29 for the mold block carriers may sit on an adjustable base 31 that allows side to side movement of the support 29 relative to the ground surface.

5

In a further embodiment of the present invention, a parison guide 39 is provided between the nozzle 6 of the extruder 3 and the mouth of the mold tunnel. This guide is again movable side to side in the horizontal plane as indicated by arrows 41 and 43.

10

Guide 39 has an opening 40 through the guide. The parison flows through and is guided by opening 40. When the guide is adjusted in a side to side direction, a corresponding adjustment is made in the flow direction of the parison from the extruder. This adjustment will correspond to the positioning of the mouth opening to the tunnel which in turn depends upon which particular set of mating mold block sections are at the upper end of the tunnel.

15

20

When working with guide 39, it may be desirable to provide a flow of fluid around the edges of the guide to prevent the parison from sticking to the guide.

25

The adjustment of the alignment of the parison flow from the extruder to the mouth of the tunnel regardless of what means is used to make that adjustment is preferably dictated by a controller within the system which is preprogrammed to make the appropriate adjustments at the appropriate times.

30

Another feature of the present invention is that the speed of the mated mold block sections through the mold tunnel can be varied by changing the speed of the carrier tracks. This in turn changes the thickness of the shaped plastic or the diameter of the part formed within the mold tunnel without changing the flow of plastic from the

35

extruder. As alternatives, the speed of the flow of plastic from the extruder can also be varied to change product wall thickness or product diameter by adjustable gaps on the extruder or by the use of adjustment screws as
5 are known in the molding art.

Although various preferred embodiments of the present invention have been described in detail, it will be appreciated by those skilled in the art, that variations
10 may be made without departing from the spirit of the invention or the scope of the appended claims.

THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. A plastic molding apparatus (1) comprising an
5 extruder (3) and a vertically extending mold tunnel (20)
formed by mated mold block sections (21, 25) which are
moved downwardly through the mold tunnel as part of a
continuous looping of the mold block sections around the
apparatus, the apparatus being characterized in that the
10 mold tunnel has an open mouth at the upper end of the
tunnel, the extruder has a nozzle (6) which is directed at
without being trapped within the mouth of the mold tunnel
and the apparatus uses vacuum to form product within the
mold tunnel.
- 15 2. A plastic molding apparatus as claimed in Claim 1,
wherein said mold block sections include sets of mated mold
block sections (21, 25) of different configurations and
wherein said tunnel mouth shifts to different positions in
20 a horizontal plane according to which set of mold blocks is
presented at a particular time at the tunnel mouth, and
said apparatus being adjustable to provide alignment of the
stream of plastic (13) with the tunnel mouth at the
different positions of the tunnel mouth.
- 25 3. A plastic molding apparatus as claimed in Claim 2,
wherein said mold block sections are moved by carrier means
(17, 19) which is mounted on and horizontally adjustable of
a support (29) for said carrier means.
- 30 4. A plastic molding apparatus as claimed in Claim 3,
wherein said carrier means comprises a pair of side by side
mold block carrier tracks (17, 19) which are horizontally
adjustable together with one another on said support.
- 35 5. A plastic molding apparatus as claimed in Claim 4,
wherein at least one of said mold block carrier tracks (17,

19) is independently adjustable on said support relative to the other of said mold block carrier tracks.

6. A plastic molding apparatus as claimed in Claim 2,
5 wherein said extruder (3) is horizontally adjustable.

7. A plastic molding apparatus as claimed in Claim 2,
including an adjustable guide (40) which is between said
extruder and said mold tunnel and which provides horizontal
10 adjustment of the stream of plastic (13) from said extruder
to the mouth of the tunnel.

8. A plastic molding apparatus as claimed in Claim 2,
wherein said carrier means (17, 19) is adjustable in speed
15 according to which set of mold block sections (21, 25) is
presented at the upper end of said mold tunnel.

9. A plastic molding apparatus as claimed in Claim 2,
including a controller which is programmed to automatically
20 adjust said apparatus to maintain feed of the stream of
molten plastic (13) into the tunnel mouth at the different
positions thereof.

1/2




FIG. 1




FIG. 2




FIG. 3




FIG. 4

TITLE: MOLDING APPARATUS WITH DOWNWARDLY MOVING MOLD TUNNELFIELD OF THE INVENTION

5 The present invention relates to a plastic mold apparatus of the type in which a continuous stream of molten plastic is fed to a moving mold tunnel.

10 BACKGROUND OF THE INVENTION

 A known molding apparatus is one in which an extruder feeds a continuous stream of molten plastic to a horizontally extending mold tunnel. This type of apparatus is very beneficial for example in a formation of plastic pipe. It is not however well suited for the formation of irregularly shaped plastic articles which require variable positioning of the feed of the plastic to the mold tunnel.

20 SUMMARY OF THE INVENTION

 The present invention provides a plastic molding apparatus comprising an extruder and a vertically extending mold tunnel formed by mated mold block sections which are moved downwardly through the mold tunnel as part of a continuous looping of the mold block sections around the apparatus. The mold tunnel has an upwardly opening tunnel mouth and the extruder feeds a stream of molten plastic downwardly into the mouth of the mold tunnel.

30 The apparatus of the present invention is particularly useful in the molding of irregularly shaped articles because either the mold tunnel and/or the extruder can be easily adjusted in position while maintaining feed of the plastic from the extruder to the mold tunnel in meeting the requirements of forming irregularly shaped plastic parts.

THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. A plastic molding apparatus comprising an extruder
5 and a vertically extending mold tunnel formed by mated mold
 block sections which are moved downwardly through said mold
 tunnel as part of a continuous looping of said mold block
 sections around said apparatus, said mold tunnel having an
 upwardly opening tunnel mouth and said extruder feeding a
10 stream of molten plastic downwardly into the mouth of the
 mold tunnel.
2. A plastic molding apparatus as claimed in Claim 1,
 wherein said mold block sections are moved by a pair of
15 side by side mold block carrier tracks.
3. A plastic molding apparatus as claimed in Claim 1,
 wherein said mold block sections include sets of mated mold
 block sections of different configurations and wherein said
20 tunnel mouth shifts to different positions in a horizontal
 plane according to which set of mold blocks is presented at
 a particular time at the tunnel mouth, and said apparatus
 being adjustable to provide alignment of the stream of
 plastic with the tunnel mouth at the different positions of
25 the tunnel mouth.
4. A plastic molding apparatus as claimed in Claim 3,
 wherein said mold block sections are moved by carrier means
 which is mounted on and horizontally adjustable of a
30 support for said carrier means.
5. A plastic molding apparatus as claimed in Claim 4,
 wherein said carrier means comprises a pair of side by side
 mold block carrier tracks which are horizontally adjustable
35 together with one another on said support.
6. A plastic molding apparatus as claimed in Claim 5,
 wherein at least one of said mold block carrier tracks is

independently adjustable on said support relative to the other of said mold block carrier tracks.

7. A plastic molding apparatus as claimed in Claim 3,
5 wherein said extruder is horizontally adjustable.

8. A plastic molding apparatus as claimed in Claim 3,
including an adjustable guide which is between said
extruder and said mold tunnel and which provides horizontal
10 adjustment of the stream of plastic from said extruder to
the mouth of the tunnel.

9. A plastic molding apparatus as claimed in Claim 3,
wherein said carrier means is adjustable in speed according
15 to which set of mold block sections is presented at the
upper end of said mold tunnel.

10. A plastic molding apparatus as claimed in Claim 1,
wherein said extruder has an extrusion nozzle which is
20 remote of said mold tunnel and wherein the plastic is
vacuum formed within the mold tunnel.

11. A plastic molding apparatus as claimed in Claim 3,
including a controller which is programmed to automatically
25 adjust said apparatus to maintain feed of the stream of
molten plastic into the tunnel mouth at the different
positions thereof.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 98/00903

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 B29C47/12 B29C49/00 B29C33/36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B29C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 134 844 A (TOYO BOSEKI) 22 August 1984 see abstract see figures 1,3,7 see page 3, line 114 - page 4, line 2 see claims 1,2,6,7	1-4,9,10
Y	---	5-7,11
Y	WO 85 01471 A (KIRCHNER FRAENK ROHR) 11 April 1985 see page 5, line 34 - page 8, line 23 see claims; figures	5-7,11
A	WO 94 09964 A (LUPKE MANFRED ARNO ALFRED) 11 May 1994 see abstract see the whole document	1-11

	-/---	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

5 February 1999

Date of mailing of the international search report

19/02/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Jensen, K

INTERNATIONAL SEARCH REPORT

In. .ational Application No

PCT/CA 98/00903

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 14 86 052 A (SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ N.V.) 3 April 1969 see page 5, line 8 - line 15 ----	1,2,10
A	US 3 519 705 A (PANNENBECKER HEINRICH) 7 July 1970 see the whole document ----	1,2
P,A	DE 197 24 857 C (UNICOR ROHRSYSTEME GMBH) 16 July 1998 see the whole document -----	1,11


INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CA 98/00903

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2134844 A	22-08-1984	JP 1679692 C	13-07-1992
		JP 3046298 B	15-07-1991
		JP 59138418 A	08-08-1984
WO 8501471 A	11-04-1985	DE 3335850 A	18-04-1985
		EP 0143278 A	05-06-1985
		JP 61500657 T	10-04-1986
		US 4674969 A	23-06-1987
WO 9409964 A	11-05-1994	CA 2081848 A	01-05-1994
		CN 1090238 A	03-08-1994
		DE 69309101 D	24-04-1997
		DE 69309101 T	25-09-1997
		EP 0670768 A	13-09-1995
		JP 8502932 T	02-04-1996
DE 1486052 A	03-04-1969	NL 6407411 A	31-12-1965
		BE 666047 A	28-12-1965
		DK 118998 B	26-10-1970
		FI 46126 B	02-10-1972
		SE 301231 B	27-05-1968
US 3519705 A	07-07-1970	BE 690798 A	07-06-1967
		DE 1479603 A	23-07-1970
		DE 1604685 A	10-02-1972
		FR 1503380 A	08-02-1968
		GB 1166506 A	08-10-1969
		LU 52508 A	07-02-1967
		NL 6617080 A	08-06-1967
DE 19724857 C	16-07-1998	NONE	



(72) LUPKE, MANFRED A.A., CA

(72) LUPKE, STEFAN A., CA

(71) LUPKE, MANFRED A.A., CA


(71) LUPKE, STEFAN A., CA

(51) Int.Cl.⁷ B29C 47/12, B29C 33/36, B29C 49/00

(30) 1997/10/03 (08/943,120) US

(54) **APPAREIL DE MOULAGE COMPORTANT UN TUNNEL
CONSTITUE DE BLOCS DE MOULAGE SE DEPLACANT
VERS LE BAS**

(54) **MOLDING APPARATUS WITH DOWNWARDLY MOVING
MOLD TUNNEL**



(57) L'invention concerne un appareil de moulage de plastique qui comprend une extrudeuse (3) et un tunnel de moulage (20) s'étendant verticalement, constitué de blocs de moulage appariés qui sont déplacés vers le bas à travers un canal de moulage, ce tunnel de moulage (20) constituant une partie d'une boucle continue de blocs de moulage s'étendant autour de l'appareil. Le tunnel de moulage (20) comporte un orifice d'alimentation tourné vers le haut et l'extrudeuse (3) injecte un courant de plastique fondu (13) dans cet orifice d'alimentation, vers le bas.

(57) A plastic molding apparatus comprises an extruder (3) and a vertically extending mold tunnel (20) formed by mated mold block sections which are moved downwardly through the mold tunnel (20) as part of a continuous looping of the mold block sections around the apparatus. The mold tunnel has an upwardly opening mouth and the extruder (3) feeds a stream of molten plastic (13) downwardly into the mouth of the mold tunnel (20).

